



eşilbayır Mah. Şimşir Sk. No: 22 Hadımköy - İstanbul/TÜRKİYE Tel: 0212 771 13 71 Fax: 0212 771 38 81/

www.akfixcoating.com - info@akfixcoating.com

AKFIX SPR 240

1-GENERAL DESCRIPTION AND APPLICATIONS

AKFIX SPR 240 PU system is designed for spray application of polyurethane foam. The material must be applied with a high pressure plural component spray polyurethane machine. Resulting foam has excellent physical properties and is classified E according to EN 13501-1. The foam stability and adhesion to the application surface is excellent. Reaction profiles are suitable for over the floor, on wall and under the ceiling.

2-CHEMICAL- PHYSICAL CHARACTERISTICS

	Unit	Polyol Blend	Isocyanate	Test Method
OH Value	MgKOH/g	260-280		ASTM D 4274
NCO Content	%		30-31	ASTM D 5155
Viscosity (25 °C)	mPa.s	260-300	220-250	ASTM D 4878
Specific Gravity (20°C)	g/ml	1,12	1,23	ASTM D 891

3-TEST VALUES

	Weight Ratio	Volumetric ratio	
Polyol blend	100	100	
Isocyanate	110	100	

	Unit of Meas.	Value	
Cream time	sec.	3-4	
Gel Time	sec.	6-8	
Tack Free Time	sec.	8-10	
Density	kg/m³	39-41	

- Polyurethane components are moisture sensitive. Therefore they must be stored at all times in sealed, closed containers.
- Polyol blend must be mixed before use.

08/2016 Rev:00 Page 1





esilbavır Mah. Simsir Sk. No: 22 Hadımköv - İstanbul/TÜRKİYE Tel: 0212 771 13 71 Fax: 0212 771 38 81/

www.akfixcoating.com - info@akfixcoating.com

4-STORAGE

	Unit	Polyol Blend	Isocyanate
Storage Temperature	°C	15-25	15-25
Shelf Life	Months	6	6

^{*}Stored in original sealed drums in a dry place at recommended temperatures.

5- PACKAGING

Polyol blend: 220 Kg Polymeric MDI: 250 Kg

6-LEGAL NOTE

The information presented herein is given in good faith but without warranty. It's based on our experience, indicates our laboratory work results and does not necessarily indicate final product performance. We cannot be held liable for the results obtained with our products and for any loss or accident that may result from its use. Our suggestions don't release you from the obligation to check their validity and to test our products for both your process and end use application.

All our products are sold in accordance with our General Conditions of Sale. We don't make any warranty, express or implied, including but not limited to the merchantability and fitness for a particular purpose.

08/2016 Rev:00 Page 2